

COAX diECi

DCX 690.3 180W

Technical Specifications


Component	-	Three way coaxial
Woofer size	mm (in.)	(6.0 x 9.0)
Tweeter size	mm (in.)	60 (2.5)
Supertweeter size	mm (in.)	15 (0.6)
Power handling	W peak	180
	W continuous	90
Impedance	Ω	4
Frequency response	Hz	45 ÷ 21k
Sensitivity	dB SPL	93
Magnet size D-d-h	mm (in.)	80 x 40 x 15 (3.1 x 1.6 x 0.6)
Voice coil Ø	mm (in.)	25 (1.0)
Woofer magnet	-	High density flux ferrite
Tweeter magnet	-	High density flux ferrite
Woofer cone	-	Water-repellent pressed paper
Tweeter cone	-	Water-repellent pressed paper
Supertweeter dome	-	PEI
Weight of one component	kg (lb.)	0,95 (2.09)

Electro-Acoustic Parameters

D	mm	170
Xmax	mm	2
Re	Ω	3,4
Fs	Hz	66
Le	mH @ 1 kHz	-
Le	mH @ 10 kHz	-
Vas	l	25,7
Mms	g	16,5
Cms	mm/N	0,35
BL	T·m	3,9
Qts	-	1,12
Qes	-	1,55
Qms	-	4,06
Spl	dB	93



1. Large motor assembly for mobile voice coil control.
2. Pure copper voice coil, wound on conex former, for maximum lightness.
3. Water-repellent treated paper cone.
4. TPU surround, for wide excursion and resonance damping.
5. 60 mm paper tweeter with ferrite magnet.
6. Supertweeter with PEI dome, for compactness and energy at high frequencies.
7. DIN size basket protected by abrasion-proof dust paint.
8. Tin-plated, high current terminals.
9. Silver-plated lead wires for maximum reliability and conductivity.
10. Butyl rubber protective cover, against crashes and abrasions.
11. Epoxy glue for basket and motor system provides perfect coupling.
12. Low carbon content plates for maximum magnetic permeability and high heat dissipation.



GRILLE

