INSTALLATION INSTRUCTIONS
Part Number: VF2012

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

*** FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal ***

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/Million mile limited warranty.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

The following instructions are for the Volkswagen Beetle:

1. Locate access panel in center of dash. Fig. 1
2. Push the panel toward the windshield, wiggling back and forth and remove panel. Fig. 2&3
3. Remove the 3 screws that attach the dash panel to in the center. Fig. 4
4. Once the screws are removed, the access panel can be removed from the vehicle. Fig. 5
5. Remove the 6 screws that hold the cabin filer access panel and remove. Fig. 6
6. Once screws are removed, pull up on access panel starting on left side and working to the right then remove. Fig. 7&8
7. Locate cabin filter tray, press in 2 tabs to remove cabin air filter & tray from housing.
8. Remove dirty cabin filter from tray. **NOTE: Remove any debris that might be present on cabin filter tray and inside the cabin filter housing. Fig 9**
9. Install K&N® Cabin Filter in tray. The indents will face up on the filter and will only fit in one direction. Once filter is installed correctly the filter will sit flush inside of tray.
10. With filter and tray together, install in cabin filter housing.
11. Reverse steps 1-7 to complete cabin filter installation. With the cabin filter installed, clean an area on the housing and apply the K&N® Stop Decal. The decal will help notify others that this is a re-usable cabin filter.


Fig. 1


Fig. 2


Fig. 3


Fig. 4


Fig. 5


Fig. 6


Fig. 7


Fig. 8


Fig. 9

Please visit our website knfilters.com for a complete listing of other K&N® products for your vehicle, such as oil filters, air filters, and intake kits. We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.

•1455 Citrus St. P.O. Box 1329, Riverside, C.A. USA 92502 • Tech Service 800-858-3333 • Fax 951-826-4001
•Email: tech@knfilters.com®• WWW: http://www.knfilters.com®

19687B
5/19/17

INSTALLATION INSTRUCTIONS
Part Number: VF2012

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

*** FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal ***

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/Million mile limited warranty.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

The following instructions are for the Volkswagen Jetta/Passat/Golf and Audi A3/TT:

1. Open the hood.
2. Remove weather stripping from the top of the firewall. Fig. 1
3. Remove the screws that attach the access panel to the firewall. Fig. 2
4. Once the screws are removed, the access panel can be removed from the vehicle. Fig. 3
5. Locate cabin filter; pressing the 2 tabs carefully lift up and remove the cabin filter tray. Fig. 4&5
6. Once dirty cabin filter is removed clean any debris that might be present on the cabin filter housing & tray.
7. Remove dirty cabin filter from tray. Fig. 6
8. Install K&N® Cabin Filter in tray. **NOTE: Place filter in tray so indent in filter will miss the 2 tabs on filter tray.** Fig 7
9. Reinstall cabin filter tray into cabin filter housing; ensure tray is locked into place. Fig. 8
10. Reverse steps 1-4 to complete cabin filter installation. With the cabin filter installed, clean an area on the housing and apply the K&N® Stop Decal. The decal will help notify others that this is a reusable cabin filter.


Fig.1


Fig.2


Fig.3






Fig.4


Fig.5


Fig.6


Fig.7


Fig.8

Please visit our website knfilters.com for a complete listing of other K&N® products for your vehicle, such as oil filters, air filters, and intake kits. We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.

•1455 Citrus St. P.O. Box 1329, Riverside, C.A. USA 92502 • Tech Service 800-858-3333 • Fax 951-826-4001
•Email: tech@knfilters.com®• WWW: http://www.knfilters.com®

19675B
5/18/17